

HI-LO SPECIFICATIONS

Description	17T	19T	22T	24T	27T	23C	25C	28C
Hydraulic Lift System	S	S	S	S	S	S	S	S
Battery 12V Heavy Duty	S	S	S	S	S	S	S	S
12 V Power Converter	45 AMP	45 AMP	45 AMP	45 AMP	45 AMP	45 AMP	45 AMP	45 AMP
Keyed Security Dead Bolt	S	S	S	S	S	S	S	S
Rubber Suspension Axles	Single	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
10" Electric Brakes All Wheels	S	S	S	S	S	S	S	S
3 burner Range Top	S	S	S	S	S	S	S	S
Range Hood w/Vent	N/A	N/A	S	S	S	S	N/A	N/A
Kitchen Sink	Single	Single	Double	Double	Double	Double	Double	Double
Demand Water System	30 Gal	30 Gal	30 Gal	30 Gal	30 Gal	30 Gal	30 Gal	30 Gal
Automatic Changeover Regulator	O	O	O	O	O	S	S	S
Skylight Roof Vent +	2	3	3	3	4	3	3	4
Skylight Dome	N/A	N/A	S	S	S	S	S	S
Sun Shade Front Window	S	S	S	S	S	S	S	S
Pleated Day/night Shades	S	S	S	S	S	S	S	S
Toilet, Shower & Water Heater	S	S	S	S	S	S	S	S
110V DSI Water Heater	O	O	O	O	O	S	S	S
Holding Tank-2	50 Gal	62 Gal	62 Gal	62 Gal	60 Gal	62 Gal	62 Gal	64 Gal
Furnace BTU	12,000	16,000	16,000	16,000	25,000	16,000	16,000	25,000
Durable Aluminum Roof	S	S	S	S	S	S	S	S
Refrigerator - 3 Way	3 cu. ft.	3 cu.ft.	4 cu. ft.	4 cu. ft.	4 cu. ft.	5 cu. ft.	5 cu. ft	5 cu. ft
Retractable Awning	O	O	O	O	O	O	O	O
Double 20 lb. Gas Bottles & Cover	S	S	S	S	S	N/A	N/A	N/A
Double 30 lb. Gas Bottles & Cover	O	O	O	O	O	S	S	S
LP Gas Oven	O	O	O	O	O	S	S	S
Microwave Oven	O	O	O	O	O	O	O	O
Air Conditioner 13,500 BTU	O	O	O	O	O	O	O	O
TV Antenna	O	O	O	O	O	S	S	S
AM/FM CD Player	O	O	O	O	O	S	S	S
Entertainment Package	O	O	O	O	O	O	O	O
Cable TV Jack & Phone Jack	O	O	O	O	O	S	S	S
Front Overhead/Side Cabinets	O	O	O	O	1-S	S	S	1-S
Swing-Away Front Bunk	O	O	O	O	N/A	O	O	N/A
Stabilizer Jacks	O	O	O	O	O	S	S	S
Power Hitch Jack	O	O	O	O	O	S	S	S
Spare Tire Package	O	O	O	O	O	S	S	S
Rear Bumper Storage	S	S	S	S	S	S	S	S
Side Storage Pods	O-3	O-3	O-3	O-3	O-3	S	S	S
Single Sink Cover	O	O	O	O	O	S	S	S
Outside Utility Shelf	S	S	S	S	N/A	N/A	N/A	N/A
Outside Washdown	O	O	O	O	O	S	S	S
Outside Light	S	S	S	S	S	S	S	S
Manual Lift System - Backup	O	O	O	O	O	S	S	S
Monitoring System	S	S	S	S	S	S	S	S
Solar Charger	O	O	O	O	O	S	S	S
2500 Watt LP Generator	O	O	O	O	O	O	O	O
Detachable Tongue	O	O	O	N/A	N/A	O	N/A	N/A
Heat Strip for A/C	O	O	O	O	O	O	O	O

GENERAL SPECIFICATIONS

Length (Does Not Include Spare)	17'9"	19"	22'4"	24'	27'9"	23' 9"	25' 5"	28'11"
Width**	94"	94"	94"	94"	94"	100"	100"	100"
Traveling Height**	71"	71"	71"	77"	77"	73"	79"	79"
Interior Height	75 ¹ / ₂ "	78"	78"	78"				
Axle Weight (lbs.) (Approx.)	2197	2310	2842	3483	3629	3473	4057	4472
Hitch Weight (lbs.) (Approx.)	300	380	490	520	760	550	660	850
Unloaded Vehicle Weight*	2497	2690	3332	4009	4379	4023	4717	5320
Tire Size	15"	15"	15"	15"	15"	15"	15"	15"
Sleeping Capacity	2-4	4-6	4-6	4-6	4	4-6	4-6	4

S - Standard
O - Optional

*Weight will vary by standard and optional features.
**Does not include projections or optional items.
+ Optional A/C replaces one roof vent.

Note: All standard and optional features are available at the time of printing. Hi-Lo, however, reserves the right to improve and/or modify the product, which may change the specifications, models and feature availability. Check with your local Hi-Lo dealer for updated information.



HI-LO - Leading the RV Industry in Safety, Durability and Livability Since 1957

HI-LO SPECIFICATIONS

SLEEPING AREA	17T	19T	22T	24T	27T	23C	25C	28C
Dinette Bed Size	36"X74"	40"X80"	36"X74"	54"X80"	N/A	39"X74"	54"X88"	N/A
Lounge Bed Size	*74"X80"	41"X74"	54"X80"	48"X72"	48"X72"	54"X80"	48"X72"	48"X72"
Bunk Bed Size	44"X84"	44"X84"	44"X84"	44"X84"	N/A	44"X90"	44"X90"	N/A
Stationary Bed	N/A	N/A	N/A	N/A	60"X75"	N/A	N/A	60"X75"

* Using dinette and lounge


**Lifetime Limited
Warranty on
Lifting System**

Hi-Lo warrants to the original purchaser that it will repair or replace (through its authorized service centers) any part of your Hi-Lo hydraulic lifting system (excluding the battery) which becomes broken or inoperative due to defects in material or workmanship. In addition, Hi-Lo warrants that it will repair or replace (through its authorized service centers) any part of your Hi-Lo travel trailer found defective due to defects in material or workmanship within 12 months from date of original purchase. (Components such as tires, running gear, power converter, battery, plumbing & electrical fixtures, refrigerator, range, etc. are subject to separate warranties issued by other manufacturers.)

Test-Tow Our Fuel Efficient Travel Trailer At Your Authorized HI-LO Dealer Today.

Visit our website at www.hilotrailer.com to find a dealer near you and locate available inventory or call the factory at 800-337-6490 for current information

Caswell RV 260 S. Dexter St. Ionia
Michigan 48846 1-800-435-0877
email.casrvco@hotmail.com
[web page. caswellrv.com](http://web.page.caswellrv.com)



HI-LO TRAILER CO.
500 South Main Street
Bellville, Ohio 44813
800-337-6490

2007 Hi-Lo Weight Specifications

	1707T	1907T	2207T	2407T
Hitch Weight	320	390	520	580
Axle Weight	2277	2400	2812	3529
UVW	2597	2790	3432	4109
CCC	1243	1100	2068	1891
GVWR	3840	3890	5500	6000
GAWR	3500	3500	3000/3000	3500/3500
Coupler Height	26"	26"	26½"	26½"

	2707T	2307C	2507C	2807C
Hitch Weight	840	560	720	960
Axle Weight	3639	3563	4097	4362
UVW	4479	4123	4817	5320
CCC	2021	1877	1483	1680
GVWR	6500	6000	6300	7000
GAWR	3500/3500	3500/3500	3500/3500	3500/3500
Coupler Height	26½"	26"	26½"	26½"

Note: All weights above are estimates, and may vary from trailer to trailer.

Steps for Determining Correct Load Limit—

1. Locate the statement "The weight of cargo should never exceed XXX kg or XXX lbs." On your vehicle's placard.
2. This figure equals the available amount of cargo and luggage load capacity.
3. Determine the combined weight of luggage and cargo being loaded on the vehicle. That weight may not safely exceed the available cargo and luggage load capacity.

2.3 Weight Distribution (continued)

Weight of optional equipment

Swing away bed	80 lbs.	Air Conditioner	105 lbs.
14 ft. Awning	93 lbs.	Spare Tire & Wheel	54 lbs.
18 ft. Awning	107 lbs.	Extra O.H. Cabinets	40 lbs.

2.4 Packing and Inspecting Trailer

Part of the fun of trailer travel and camping is the ability to take along recreational equipment such as a boat, motor, fishing gear and sports equipment. Comfort items such as awnings, folding tables, and chairs add to your camping pleasure. And, you will certainly want to include some of the foodstuffs from your own kitchen. Also, be sure to fill your water tank.

Although your Hi-Lo trailer is sturdily built with margins of safety, too much extra weight can damage the undercarriage and cause excessive tire wear. Check label GW on the left front corner for maximum Gross Vehicle Weight.

Your Hi-Lo trailer is designed and balanced for easier and safer towing so that just the right tongue weight rests on the car hitch. In packing extra equipment, it is important to maintain that balance as near as possible fore and aft. It is also recommended that the heaviest item to be positioned as near as possible to directly over the wheels. In stowing loose equipment, pack it in such a way as to avoid shifting during acceleration or braking. Pad heavy and sharp items to avoid damaging interiors and equipment. A little extra care and a few minutes spent in getting your trailer ready for travel assures a pleasant trip.

2.5 Vehicle Inspection

Your vehicle should be in good running order. Also tires, lights, and brakes should be checked before travel.

2.6 Be sure waste holding tanks are empty. (See 8.9)

The above weights are approximate weights of standard models. Add for optional items if applicable:

GVWR (Gross Vehicle Weight Rating) means the maximum permissible weight of this trailer. The GVWR is equal to or greater than the sum of the Unloaded Vehicle Weight plus the Net Carrying Capacity.

UVW (Dry or Unloaded Vehicle Weight) means the weight of this trailer as built at the factory. If applicable, it includes full generator fuel, engine oil, and coolants. The UVW does not include cargo, fresh water, LP gas, or dealer installed accessories.

CCC (Cargo Carrying Capacity) means the maximum weight of all personal belongings, food, fresh water, LP gas, tools, dealer installed accessories, etc, that can be carried by this trailer. (NCC is equal to or less than GVWR minus UVW).

This trailer is capable of carrying up to 36 gallons of fresh water (including water heater) for a total of 300 pounds. Reference: Weight of fresh water is 8.33 lbs/gal; Weight of propane is 4.5 lbs/gal (average).