

PREPARING TO LEAVE CAMP

| Interior Exterior | Item | Done |
|----------------------|--|------|
| E | Stow all camping gear, chairs, BBQ, tools, etc. in Tahoe | |
| E | Drain and flush holding tanks, if hooked up or dump on the way out | |
| E | Remove and rinse sewer hose- stow in bumper | |
| E | Fill FW tank, if desired, and remove water line and stow. Secure city water/ FW tank fill caps | |
| E | Remove and stow electrical power cord | |
| E | Shut off propane tank(s) | |
| E | Shut front window rockguard and latch | |
| E | Ensure TV antenna is down | |
| E | Verify awning is properly stowed: check that locks and knobs are tight | |
| I | Turn oven pilot to "off" position. | |
| I | Turn off water heater | |
| I | Turn off furnace | |
| I | Shut off water pump and fridge fan switches | |
| I | Change fridge to 12V setting for transit, or turn off | |
| I | Unplug Air Conditioning cord in bathroom | |
| I | Close toilet lid and snap bathroom door shut | |
| I | Close all windows and secure blinds | |
| I | Close both vents | |
| I | Close all cabinet doors | |
| I | Secure loose items and clear all counters | |
| I | Center kitchen faucet over sink and close drains | |
| I | Close shower and sink drains | |
| I | Clear area in front of sofa to facilitate stowing tip-out | |
| I | Stow swing-away bunk, if applicable | |
| I | Ensure furnace and water heater switches are off | |
| I | Turn off all lights | |
| E | Verify no one is inside trailer | |
| E | Retract tip-out: 1. Place black master switch in lower position 2. Press tip-out toggle switch up - when winch stops, let go of switch immediately 3. Go into coach and pull tip-out down until it stops 3. Press tip-out switch down until fully retracted, then let go of switch immediately | |
| E | Secure exterior straps for tip-out | |
| E | Raise stabilizer jacks and stow handle in front curbside compartment | |
| E | Walk around trailer to check for any obstructions or open access doors, caps, etc. Verify all utilities are disconnected | |
| E | Lower Trailer: 1. Press white rocker switch up briefly to ensure locking pin is free 2. Pull the release cable out 3. Press the white rocker switch down , then release the cable. Let go of switch when trailer is fully lowered | |
| E | Close doors securely and lock upper door | |
| E | Put step in travel position | |
| E | Hitch to tow vehicle | |
| E | Test breakaway switch by pulling out pin and attempting to drive forward. Brakes should be activated (do this before plugging in trailer electrical cable) | |
| E | Plug in trailer electrical cable | |
| E | Verify blinkers, tail lights, brake lights, and marker lights are working | |
| E | Remove wheels chocks and stow in Tahoe | |
| E | Roll off levelers and stow in Tahoe | |

| | | |
|---|--|--|
| E | Check Tahoe tires and fluids | |
| E | Check trailer tires @ 65 psi | |
| E | Check mirror adjustment | |
| E | Dump tanks, if applicable. Rinse and stow hose in bumper | |
| | | |